



TABLA DE SELECCIÓN DE FILTROS

MODELO	DIÁMETRO INTERIOR mm	ÁREA DE FILTRADO m ²	VELOCIDAD DE FILTRADO m ³ / m ² / h	CAUDAL FILTRADO m ³ / h	VOLUMEN DE FILTRACIÓN (m ³)					BOMBA RECOMENDADA	
					4 h	6 h	8 h	10 h	12 h	Modelo	Potencia
VC10	280	0,062	50	3,10	12	19	25	31	37	BAE, BAP, BAS	0,33HP
VC20	350	0,096	50	4,80	19	29	38	48	58	BAE, BAP, BAS	0,33HP
VC30	430	0,145	50	7,25	29	44	58	73	87	BAE, BAP, BAS, BAT	0,50HP
VC50	530	0,221	50	11,05	44	66	88	111	133	BAE, BAP, BAT	0,75HP
VC100	660	0,342	50	17,10	68	103	137	171	205	BAE, BAP, BAT	1,00HP
										BAE, BAP	1,25HP
										BAC	1,50HP
VC200	740	0,430	50	21,50	86	129	172	215	258	BAC	2,00HP

VC10



680



ø 290

VC20



750



ø 360

VC30




800



ø 440

VC50




900



ø 540

VC100



970



ø 690

www.vulcano-sa.com